



Base code	A. Wattage	B. Kelvin	C. Beam
DUE	08 - 8.5 W	27 - 2700K 30 - 3000K 40 - 4000K	W - 40°

Base code A B C D E

Example: **DUE - 08 30 W G-B DA = DUE S - 08 30 W G-B DA**

#### D. Reflector & Trim finish

G-B  
BG-B  
SG-B  
W-B  
C-B

G-W  
BG-W  
SG-W  
W-W  
C-W


#### E. Dimming option

ND - Non Dim  
PC - Phase-cut  
AD - Analog  
DA - Dali  
D2 - Dali 2  
WD - Dim to warm  
CS - Casambi

## SPECIFICATIONS

base code	DUE
typology	Recessed adjustable LED luminaire, Installation frame included.
construction	Aluminum Die Cast
reflector finish	Gold (G), Black High Gloss (BG), Silver High Gloss (SG), White (W), Chrome (C)
trim finish	Black (B)/ White (W)
lamp wattage	8.5W
delivered lumens	830lm / 860lm / 870lm
CCT	2700K / 3000K / 4000K
beam	40°
binning	< 2
CRI	> 90
life	50.000h
IP	IP20
special features	Variable combination between single, double, triple, quadruple can be made using specific installation frames as shown below
dimming options	Phase-cut Dim, 0-10V, DALI, CASAMBI, Dim to Warm. Power supply to be ordered separately

#### dimension



#### installation frames

