BConnect

Roa

SPECIFICATIONS

base code	ROA
typology	Recessed adjustable LED luminaire, Installation frame included
construction	Aluminum Die Cast
reflector finish	Gold (G), Black High Gloss (BG), Silver High Gloss (SG), White (W), Chrome (C)
trim finish	Black (B) / White (W)
lamp wattage	6.2W
delivered lumens	490lm / 500lm / 510lm
CCT	2700K / 3000K / 4000K
beam	34°
binning	< 2
CRI	> 90
life	50.000h
IP	IP20
special features	Variable combination between single, double, triple, quadruple can be made using specific installation frames as shown below
dimming options	Phase-cut Dim, 0-10V, DALI, CASAMBI, Dim to Warm. Power supply to be ordered separately
dimension	
installation frames	

Single frame | Double frame | Triple frame | Quadruple frame | Quadruple Square frame

Base code	A. Wattage	B. Kelvin	C. Beam
ROA	06 - 6.2 W	27 - 2700K 30 - 3000K 40 - 4000K	M - 34°

Example: ROA - (Base code) 06 (A) 30 (B) M (C) G-B (D) DA (E) = ROA XS - 06 30 M G-B DA

D. Reflector & Trim finish		E. Dimming option
G-B	G-W	ND - Non Dim
BG-B	BG-W	PC - Phase-cut
SG-B	SG-W	AD - Analog
W-B	W-W	DA - Dali
C-B	C-W	D2 - Dali 2
		WD - Dim to warm
		CS - Casambi